



Inbuilt AC/DC SPD's with DC fuse etc..



Suitable for high watt peak panels
Mono Perc, TOPCon & Bifacial.



IP65 & IP66 Dynamic intelligent cooling
& String level monitoring.



100% Inhouse R&D, Production &
testing Facility at Pune.



Individual String Level Monitoring
RMS Available

60KW-110KW Three Phase

DATASHEET



	Three Phase (60KW - 110KW)						
Model (KSY)(KW)	60	70	75	80	90	100	110
Input (DC)							
Max Peak DC Input Power (kW)	72	84	90	96	100	120	130
Max. DC I/P (V dc)	1100Vdc						
Max. MPPT I/P Current (A)	36A		48A & 36A		60A		
MPPT Short Circuit Current (A)	45A		60A & 45A		75A		
MPPT Tracking Voltage (Vdc)	250-1000V						
Min. Start Voltage (V)	250VDC						
Number of MPPT Tracker	4						
Strings per MPPT Trackers	3		4+3		5		
Strings Level Monitoring	Inbuilt						
Output (AC)							
Rated output power (kw)	60	70	75	80	90	100	110
Rated Grid Voltage (V)	400V (300V - 500V)						
Nominal Grid Freq.(Hz)	50Hz/60Hz						
Max. output Current AC (A)	86.7	101.2	108.4	115.6	130.1	144.5	159.0
AC Connection (With PE)	3P + N + E / 3P + E						
THDI (%)	<3% (At Rated Power)						
Output Power Factor (%)	0.8 Leading... 1... 0.8 Lagging						
Efficiency							
Max. Conversion Eff.(%)	98.9						
Max. Euro Efficiency (%)	98.5						
General Data							
Dimensions(W*H*D) mm	705*650*283mm				800*672*315mm		
Weight (Kg)	75kg				85kg		
Noise Emission (db)	<60dB						
Display	LED Indications for IP66 / LCD Optional						
DC Connection Type	MC-4						
AC Connection Type	Terminal Block						
Communication Interface	WiFi/ GPRS/ RS 485 / String level Monitoring						
Cooling Method	Intelligent Force Cooling + Natural Cooling						
Operating Ambient	- 25°C - +60°C						
Relative Humidity	0% - 100%						
Max. Operating Altitude(m)	5000 (>4000 Derating)						
Protection Class	IP66 / IP65						
Night Stand By Power Consumption (w)	<5						
Standard Warranty	8 Years						
Protection							
Safety Standard	Yes Integrated						
Environment Protections	Yes Integrated						
Anti-Islanding Protection	Yes Integrated						
Insulation Resistance Detection	Yes Integrated						
Residual Current Monitoring	Integrated / Inbuilt						
DC Switch	Supported						
Surge Protection	DC/AC : Type II (DC Fuse)						

Call:9825058062

*BIS ,IEC 62109 -1/2, IEC 61727, IEC 61683, IEC 60068, IEC 62116, IEC 61000 EMC

Note - All specification are subject to change without notice due to continuous upgradation in Modules Wp capacity

